

# ICS CORE DRILL STAND

PRODUCT DATASHEET  
DPT-L250-2-ICS

DPT-L250-2-ICS  
FOR DPT MICRO-PERCUSSION



**FITS:**  
DPT2200-ME-36-120V  
DPT2200-SE-36-120V  
DPT3000-ME-37-120V

## Specifications

|  |   |
|--|---|
| Base                                   | High Resistance Aluminum Base   |
| Column                                 | Extruded Aluminum 2" x 2" / 5 cm x 5 cm                               |
| Carriage                               | Self Lubricating Sliding Pads   |
| Feeding Handle                         | DPT Anti-Vibration Technology<br>Vibrations reduced by 50%            |
| Max Carriage Run                       | 28.25" / 72 cm  |
| Rear Bars                              | Steel - 2 Bars  |
| Tilting Angle                          | From 0° - 45°   |
| Fixing System                          | With Anchor   |
| Core Drill Mounting                    | 60 mm Collar for Hand-Held Core Drills<br>Rapid Quick-Lock Connection |
| Max Drilling Diameter                  | 12" / 30 cm   |
| Weight                                 | 381 lbs / 17.3 kg   |
| Dimensions L x W x H                   | 22.5" x 14.25" x 40" / 47 cm x 36 cm x 101 cm                         |
| Includes 19mm Spanner & 6 mm Allen Key |   |

Core Drill, Stand and  
Core bit sold separately



Diamond Tools and Equipment

ICSDIAMONDTOOLS.COM | 800.321.1240

Effective January 1, 2025 | Copyright 2025 ICS, Oregon Tool Inc. Pricing, product offerings and specifications are subject to change without notice. FORCE3, FORCE4, PowerGrit, SpeedHook, SealPRO, and WallWalker are registered trademarks of ICS. The best way to cut concrete, DCT, Speed King, TSS, Trident and ProFORCE are trademarks of ICS. Rev: 012025.