

ICS CORE DRILL

PRODUCT DATASHEET
DPT3000-ME-37-120V

DPT3000-ME-37-120V
HANDHELD OR ON STAND
MICRO PERCUSSION TECHNOLOGY
AIR COOLED



**40% faster
than drills
without DPT**



Specifications

**FITS STANDS:
DPT-L200-2-ICS
DPT-L250-2-ICS**

Drilling Diameter	.75" - 12" / 2 - 30 cm
Input Power (Max/Rated)	2850 / 2300 W
Input Current (Max/ Rated)	25 / 20 A
Operational Mode	Hand-held or on stand (rig)
Drilling Mode	Advanced hybrid wet/dry
MotorType	Electric 1P 115-120V - 50-60 Hz
Gears	3
Rated No-Load rpm	640 / 1200 / 1770 RPM
Rated Load rpm	470 / 870 / 1290 RPM
Core Bit Connection	1.25" UNC
Noise Emissions - Sound Pressure Level (LpA)	97 [dB (A)]
Noise Emissions - Sound Power Level (LWA)	108 [dB (A)]
Vibrations Value - Drilling into Concrete (ah, DD)	3.64 [m/s ²]
Vibrations Value - Impact Drilling into concrete (ah, ID)	13.78 [m/s ²]
Weight	19 lbs / 8.6 kg
Dimensions L x W x H	21.25" x 4" x 6.75" / 56 cm x 12 cm x 18 cm
Includes Heavy Duty Plastic Carrying Case. 32mm Spanner	



Diamond Tools and Equipment

ICSDIAMONDTOOLS.COM | 800.321.1240

Effective January 1, 2025 | Copyright 2025 ICS, Oregon Tool Inc. Pricing, product offerings and specifications are subject to change without notice. FORCE3, FORCE4, PowerGrit, SpeedHook, SealPRO, and WallWalker are registered trademarks of ICS. The best way to cut concrete, DCT, Speed King, TSS, Trident and ProFORCE are trademarks of ICS. Rev: 012025.

ICS CORE DRILL STAND

PRODUCT DATASHEET
DPT-L250-2-ICS

DPT-L250-2-ICS
FOR DPT MICRO-PERCUSSION



FITS
DPT2200-ME-36-120V
DPT2200-PE-36-120V
DPT3000-ME-37-120V

Core Drill, Stand and
Core bit sold separately

Specifications

Base	High Resistance Aluminum Base
Column	Extruded Aluminum 2" x 2" / 5 cm x 5 cm
Carriage	Self Lubricating Sliding Pads
Feeding Handle	DPT Anti-Vibration Technology Vibrations reduced by 50%
Max Carriage Run	28.25" / 72 cm
Rear Bars	Steel - 2 Bars
Tilting Angle	From 0° - 45°
Fixing System	With Anchor
Core Drill Mounting	60 mm Collar for Hand-Held Core Drills Rapid Quick-Lock Connection
Max Drilling Diameter	12" / 30 cm
Weight	38.1 lbs / 17.3 kg
Dimensions L x W x H	22.5" x 14.25" x 40" / 47 cm x 36 cm x 101 cm
Includes 19mm Spanner & 6 mm Allen Key	



Diamond Tools and Equipment

ICSDIAMONDTOOLS.COM | 800.321.1240

Effective January 1, 2025 | Copyright 2025 ICS, Oregon Tool Inc. Pricing, product offerings and specifications are subject to change without notice. FORCE3, FORCE4, PowerGrit, SpeedHook, SealPRO, and WallWalker are registered trademarks of ICS. The best way to cut concrete, DCT, Speed King, TSS, Trident and ProFORCE are trademarks of ICS. Rev: 012025.